Declaration of Performance
SABA Ecoseal

adhesives & sealants

Number: 101096/040614

1. Unique identification code: SABA Ecoseal
2. Batch number: Printed on packaging
3. Intended use: Sealant for facade elements.
4. Manufacturer: SABA Dinxperlo BV
   Industriestraat 3 NL-7091 DC Dinxperlo
   The Netherlands, T +31 (0)315 65 89 99
5. Authorized representative: N/A
6. Systems of assessment of performance: System 3
7. Harmonized standard: EN 15651-1, Type F 25LM INT-EXT
8. Notified body: N/A
9. Declared performance

Pre-conditioning: Method B		
Substrate: Concrete with SABA Primer 9002		
Essential characteristic	**Performance**	**Technical specification**
Reaction to fire	Class E	EN 15651-1: 2012
Release of chemicals dangerous to the environment and health	See MSDS	EN 15651-1: 2012
Water tightness and air tightness:		
Resistance to flow	⩽ 2 mm	EN 15651-1: 2012
Volume loss	⩽ 10%	EN 15651-1: 2012
Adhesion and cohesion properties at maintained extension after immersion in water	Pass	EN 15651-1: 2012
Secant tensile modulus (100%) at -30 ºC	NPD	EN 15651-1: 2012
Tensile properties at maintained extension at -30 ºC	NPD	EN 15651-1: 2012
Durability	Pass	EN 15651-1: 2012

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



SABA Dinxperlo BV
Drs. R.F. de Block, Chief Technology Officer

CE

SABA Dinxperlo BV, Industriestraat 3 NL-7091 DC Dinxperlo
The Netherlands, T +31 (0)315 65 89 99

14

DoP: 101096/040614

SABA Ecoseal, EN 15651-1, Type F 25LM INT-EXT

Sealant for facade elements.

Pre-conditioning: Method B	
Substrate: Concrete with SABA Primer 9002	
Essential characteristic	**Performance**
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	See MSDS
Water tightness and air tightness:	
Resistance to flow	⩽ 2 mm
Volume loss	⩽ 10%
Adhesion and cohesion properties at maintained extension after immersion in water	Pass
Secant tensile modulus (100%) at -30 ºC	NPD
Tensile properties at maintained extension at -30 ºC	NPD
Durability	Pass

SABA Dinxperlo BV
Industriestraat 3 NL-7091 DC Dinxperlo • PO Box 3 NL-7090 AA Dinxperlo
T +31 (0)315 65 89 99 • F +31 (0)315 65 32 07 • Trade register Arnhem 09065419 • info@saba-adhesives.com • **www.saba-adhesives.com**

Our recommendations and instructions for use are based on current knowledge and technology. Customers and users must make their own assessment of our products with regard to their desired utilization and requirements. We are not liable if our products are not used according to our recommendations and/or instructions for use. Our general terms and conditions apply to all requests, instructions for use, quotations, orders, and agreements. These general terms and conditions have been filed with the Arnhem Chamber of Commerce under number 09065419 and can also be consulted on our website at www.saba-adhesives.com. At your request, a copy of these terms and conditions will be sent to you free of charge. The general terms and conditions incorporate a limitation of SABA Dinxperlo BV's liability, as well as the choice of Dutch law as the applicable law and choice of the courts of the Netherlands as the forum. Any disputes ensuing from or relating to requests, instructions for use, quotations, orders, and agreements of SABA Dinxperlo BV must be brought before the competent court in the district were SABA Dinxperlo BV is based.
Version number 2018/05/07, this supersedes all previous versions