

Declaration of Performance Sababuild® 650



Number: 101115/230414

1. Unique identification code: Sababuild® 650
2. Batch number: Printed on packaging
3. Intended use: Sealant for facade elements.
4. Manufacturer: SABA Dinxperlo BV
Industriestraat 3 NL-7091 DC Dinxperlo
The Netherlands, T +31 (0)315 65 89 99
5. Authorized representative: N/A
6. Systems of assessment of performance: System 3
7. Harmonized standard: EN 15651-1, Type F 25LM INT-EXT
8. Notified body: N/A
9. Declared performance

Pre-conditioning: Method B

Substrate: Concrete with SABA Primer 9002

| Essential characteristic | Performance | Technical specification |
|---|-------------|-------------------------|
| Reaction to fire | Class E | EN 15651-1: 2012 |
| Release of chemicals dangerous to the environment and health | See MSDS | EN 15651-1: 2012 |
| Water tightness and air tightness: | | |
| Resistance to flow | ≤ 2 mm | EN 15651-1: 2012 |
| Volume loss | ≤ 10% | EN 15651-1: 2012 |
| Adhesion and cohesion properties at maintained extension after immersion in water | Pass | EN 15651-1: 2012 |
| Secant tensile modulus (100%) at -30 °C | NPD | EN 15651-1: 2012 |
| Tensile properties at maintained extension at -30 °C | NPD | EN 15651-1: 2012 |
| Durability | Pass | EN 15651-1: 2012 |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

SABA Dinxperlo BV
Drs. R.F. de Block, Chief Technology Officer



SABA Dinxperlo BV, Industriestraat 3 NL-7091 DC Dinxperlo
The Netherlands, T +31 (0)315 65 89 99

14

DoP: 101115/230414

Sababuild® 650, EN 15651-1, Type F 25LM INT-EXT

Sealant for facade elements.

Pre-conditioning: Method B

Substrate: Concrete with SABA Primer 9002

| Essential characteristic | Performance |
|---|-------------|
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | See MSDS |
| Water tightness and air tightness: | |
| Resistance to flow | ≤ 2 mm |
| Volume loss | ≤ 10% |
| Adhesion and cohesion properties at maintained extension after immersion in water | Pass |
| Secant tensile modulus (100%) at -30 °C | NPD |
| Tensile properties at maintained extension at -30 °C | NPD |
| Durability | Pass |

SABA Dinxperlo BV

Industriestraat 3 NL-7091 DC Dinxperlo • PO Box 3 NL-7090 AA Dinxperlo

T +31 (0)315 65 89 99 • F +31 (0)315 65 32 07 • Trade register Arnhem 09065419 • info@saba-adhesives.com • www.saba-adhesives.com

Our recommendations and instructions for use are based on current knowledge and technology. Customers and users must make their own assessment of our products with regard to their desired utilization and requirements. We are not liable if our products are not used according to our recommendations and/or instructions for use. Our general terms and conditions apply to all requests, instructions for use, quotations, orders, and agreements. These general terms and conditions have been filed with the Arnhem Chamber of Commerce under number 09065419 and can also be consulted on our website at www.saba-adhesives.com. At your request, a copy of these terms and conditions will be sent to you free of charge. The general terms and conditions incorporate a limitation of SABA Dinxperlo BV's liability, as well as the choice of Dutch law as the applicable law and choice of the courts of the Netherlands as the forum. Any disputes ensuing from or relating to requests, instructions for use, quotations, orders, and agreements of SABA Dinxperlo BV must be brought before the competent court in the district where SABA Dinxperlo BV is based.

Version number 2018/05/07, this supersedes all previous versions