

Declaration of Performance Sabaseal



Number: 450202/130220

1. Unique identification code: Sabaseal
2. Batch number: Printed on packaging
3. Intended use:
 - Sealant for facade elements.
 - Sealants for glazing.
 - Sealants for sanitary joints.
4. Manufacturer: SABA Dinxperlo BV
Meniststraat 7 NL-7091 ZZ Dinxperlo
The Netherlands, T +31 (0)315 65 89 99
5. Authorized representative: N/A
6. Systems of assessment of performance: System 3
7. Harmonized standard:
 - EN 15651-1, Type F 25LM INT-EXT-CC
 - EN 15651-2, Type G 25LM CC
 - EN 15651-3, Type XS1
8. Notified body: N/A
9. Declared performance

Pre-conditioning: Method A


Substrate: Glass and aluminium without primer, concrete with primer

Essential characteristic	Performance	Technical specification
Reaction to fire	Class E	EN 15651-1: 2012, EN 15651-2 & EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	See SDS	EN 15651-1: 2012, EN 15651-2 & EN 15651-3: 2012
Water tightness and air tightness:		
Resistance to flow	≤ 2 mm	EN 15651-1: 2012, EN 15651-2 & EN 15651-3: 2012
Volume loss	≤ 10%	EN 15651-1: 2012, EN 15651-2 & EN 15651-3: 2012
Adhesion and cohesion properties at maintained extension after immersion in water	Pass	EN 15651-1: 2012 & EN 15651-3: 2012
Secant tensile modulus (100%) at -30 °C	NPD	EN 15651-1: 2012 & EN 15651-2: 2012
Tensile properties at maintained extension at -30 °C	NPD	EN 15651-1: 2012 & EN 15651-2: 2012
Elastic recovery	≥ 70%	EN 15651-2: 2012
Adhesion and cohesion properties after exposure to artificial light	Pass	EN 15651-2: 2012
Microbiological growth	1	EN 15651-3: 2012
Durability	Pass	EN 15651-1: 2012, EN 15651-2 & EN 15651-3: 2012

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



SABA Dinxperlo BV
Drs. R.F. de Block, Chief Technology Officer



SABA Dinxperlo BV, Meniststraat 7 NL-7091 ZZ Dinxperlo
The Netherlands, T +31 (0)315 65 89 99

20

DoP: 450202/130220

Sabaseal, EN 15651-1, Type F 25LM INT-EXT-CC / EN 15651-2, Type G 25LM CC / EN 15651-3, Type XS1

Sealant for facade elements. / Sealants for glazing. / Sealants for sanitary joints.

Pre-conditioning: Method A	
Substrate: Glass and aluminium without primer, concrete with primer	
Essential characteristic	Performance
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	See SDS
Water tightness and air tightness:	
Resistance to flow	≤ 2 mm
Volume loss	≤ 10%
Adhesion and cohesion properties at maintained extension after immersion in water	Pass
Secant tensile modulus (100%) at -30 °C	NPD
Tensile properties at maintained extension at -30 °C	NPD
Elastic recovery	≥ 70%
Adhesion and cohesion properties after exposure to artificial light	Pass
Microbiological growth	1
Durability	Pass

SABA Dinxperlo BV

Meniststraat 7 NL-7091 ZZ Dinxperlo • PO Box 3 NL-7090 AA Dinxperlo
T +31 (0)315 65 89 99 • F +31 (0)315 65 32 07 • Trade register Arnhem 09065419 • info@saba-adhesives.com • www.saba-adhesives.com

Our recommendations and instructions for use are based on current knowledge and technology. Customers and users must make their own assessment of our products with regard to their desired utilization and requirements. We are not liable if our products are not used according to our recommendations and/or instructions for use. Our general terms and conditions apply to all requests, instructions for use, quotations, orders, and agreements. These general terms and conditions have been filed with the Arnhem Chamber of Commerce under number 09065419 and can also be consulted on our website at www.saba-adhesives.com. At your request, a copy of these terms and conditions will be sent to you free of charge. The general terms and conditions incorporate a limitation of SABA Dinxperlo BV's liability, as well as the choice of Dutch law as the applicable law and choice of the courts of the Netherlands as the forum. Any disputes ensuing from or relating to requests, instructions for use, quotations, orders, and agreements of SABA Dinxperlo BV must be brought before the competent court in the district where SABA Dinxperlo BV is based.

Version number 2022/11/16, this supersedes all previous versions